



Certificate / Certificat Zertifikat / 合格証

HAF 1511126 C001

exida hereby confirms that the:

**Mechanically actuated valves
Direct operated solenoid valves
Pneumatically operated valves
Pilot operated solenoid valves**

**HAFNER Pneumatika Kft.
Halászi, Hungary**

Have been assessed per the relevant requirements of:

IEC 61508 : 2010 Parts 1-7

and meets requirements providing a level of integrity to:

Systematic Capability: SC 3 (SIL 3 Capable)

Random Capability: Type A, Route 2_H Device

**PFD_{AVG} and Architecture Constraints
must be verified for each application**

Safety Function:

The valve will move to the designed safe position when de-energized / energized within the specified safety time.

Application Restrictions:

The valve must be properly designed into a Safety Instrumented Function per the Safety Manual requirements.



Peter L.
Evaluating Assessor

J. Hollmann
Certifying Assessor

The manufacturer
may use the mark:



Revision 3.1 Jan 30, 2024
Surveillance Audit Due
Feb 1, 2027



HAF 1511126 C001

Systematic Capability: SC 3 (SIL 3 Capable)

Random Capability: Type A, Route 2_H Device
PFD_{AVG} and Architecture Constraints
must be verified for each application

Systematic Capability :

The products have met manufacturer design process requirements of Safety Integrity Level (SIL) 3. These are intended to achieve sufficient integrity against systematic errors of design by the manufacturer.

A Safety Instrumented Function (SIF) designed with these products must not be used at a SIL level higher than stated.

Random Capability:

The SIL limit imposed by the Architectural Constraints must be met for each element. These devices meets *exida* criteria for Route 2_H

IEC 61508 Failure Rates:

The failure rates for the assessed valves are found in the document:
HAFNER 1511-126-C Annex to certificate R004 V3 R1.

SIL Verification:

The Safety Integrity Level (SIL) of an entire Safety Instrumented Function (SIF) must be verified via a calculation of PFD_{AVG} considering redundant architectures, proof test interval, proof test effectiveness, any automatic diagnostics, average repair time and the specific failure rates of all products included in the SIF. Each element must be checked to assure compliance with minimum hardware fault tolerance (HFT) requirements.

The following documents are a mandatory part of certification:

Assessment Report: HAFNER 15/11-126-C R003 Assessment report V3 R1

Safety Manual : HAFNER Safety Manual V1 R1



Mechanically actuated valves
Direct operated solenoid valves
Pneumatically operated valves
Pilot operated solenoid valves



Annex to certificate HAF 1511126 C001

Project:

Mechanically actuated valves, direct operated solenoid valves,
pneumatically operated valves and pilot operated solenoid valves

Customer:

HAFNER Pneumatika Kft.
Halászi
Hungary

Contract Number: Q15/11-126-C

Report No.: Q15/11-126-C R004

Version V3, Revision R1, January 2024

Peter Söderblom



Table of Contents

1	Purpose and Scope	3
2	Variants	3
2.1	Failure rates	13
3	Status of the Document	14
3.1	Liability	14
3.2	Releases	14
3.3	Future Enhancements	14
3.4	Release Signatures	14

1 Purpose and Scope

This document lists the versions of the assessed valves together with their respective failure rates. Normally these are registered on the certificate itself but as this assessment was performed for so many variants, the numbers are maintained in this annex instead.

2 Variants

The mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves can be considered to be part of a Type A element with a hardware fault tolerance of 0.

Tables 1 – 16 gives an overview of the different variants that belong to the considered mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves.

For safety applications only the described variants in Tables 1 - 16 of of the mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves working as DTT (De-energize To Trip) devices have been considered.

Table 1: [V1] Mechanically actuated 3/2-way valves

Name	Description
BR 311 ...	Mechanically actuated 3/2-way roller lever valves
BR 311 ... VES	Mechanically actuated 3/2-way roller lever valves, stainless steel
BV 311 ...	Mechanically actuated 3/2-way stem valves
BV 311 ... VES	Mechanically actuated 3/2-way stem valves, stainless steel
BV 311 ... TT	Mechanically actuated 3/2-way stem valves for low temperature (with unidirectional sealing)
BL 311 ...	Mechanically actuated 3/2-way roller lever valves with idle return
BG 311 ...	Mechanically actuated 3/2-way stem actuated spool valves
BG 311 ... TT	Mechanically actuated 3/2-way stem actuated spool valves for low temperature (with unidirectional sealing)
BG 311 ... TT AIR	Mechanically actuated 3/2-way stem actuated spool valves for low temperature (with bidirectional sealing)

Table 2 [V2] Mechanically actuated 5/2-way valves

Name	Description
BR 511 ...	Mechanically actuated 5/2-way roller lever valves
BR 511 ... VES	Mechanically actuated 5/2-way roller lever valves, stainless steel
BV 511 ...	Mechanically actuated 5/2-way stem valves
BV 511 ... VES	Mechanically actuated 5/2-way stem valves, stainless steel
BV 311 ... TT	Mechanically actuated 3/2-way stem valves for low temperature (with unidirectional sealing)
BL 511 ...	Mechanically actuated 5/2-way roller lever valves with idle return

Table 3 [V3] Direct operated 2/2-way and 3/2-way solenoid valves

Name	Description
M... 211 ...	Direct actuated in-line 2/2-way solenoid valves
M... 211 ... VES	Direct actuated in-line 2/2-way solenoid valves, stainless steel
M... 311 ...	Direct actuated in-line 3/2-way solenoid valves
M...311 ... VES	Direct actuated in-line 3/2-way solenoid valves, stainless steel
M... 311 ... TT	Direct actuated in-line 3/2-way solenoid valves for low temperature (with unidirectional sealing)

Table 4 [V4] Pneumatically operated 2/2-way and 3/2-way valves

Name	Description
P... 210 ...	Pneumatically actuated 2/2-way spool valves
P... 211 ...	Pneumatically actuated 2/2-way spool valves with mechanical spring return
P... 210 ... VES	Pneumatically actuated 2/2-way spool valves, stainless steel
P... 211 ... VES	Pneumatically actuated 2/2-way spool valves with mechanical spring return stainless steel
P... 210 ... TT	Pneumatically actuated 2/2-way spool valves for low temperature (with unidirectional sealing)
P... 211 ... TT	Pneumatically actuated 2/2-way spool valves with mechanical spring return (with unidirectional sealing)
P... 210 ... VIT	Pneumatically actuated 2/2-way spool valves with FPM/FKM sealings
P... 211 ... VIT	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P... 210 ... NT	Pneumatically actuated 2/2-way spool valves for -20°C
P... 211 ... NT	Pneumatically actuated 2/2-way spool valves with mechanical spring return for -20°C
P... 211 ... SR	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch
P... 211 ... SR VIT	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch with FPM/FKM sealings
P... 211 ... SR NT	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -20°C
P... 211 ... SR 02 NTB	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -25°C
P... 310 ...	Pneumatically actuated 3/2-way spool valves
P... 311 ...	Pneumatically actuated 3/2-way spool valves with mechanical spring return
P... 310 ... VES	Pneumatically actuated 3/2-way spool valves, stainless steel
P... 311 ... VES	Pneumatically actuated 3/2-way spool valves with mechanical spring return stainless steel
P... 310 ... TT	Pneumatically actuated 3/2-way spool valves for low temperature (with unidirectional sealing)
P... 311 ... TT	Pneumatically actuated 3/2-way spool valves with mechanical spring return (with unidirectional sealing)
P... 310 ... TT AIR	Pneumatically actuated 3/2-way spool valves for low temperature (with bidirectional sealing)

Name	Description
P... 311 ... TT AIR	Pneumatically actuated 3/2-way spool valves with mechanical spring return (with bidirectional sealing)
P... 310 ... VIT	Pneumatically actuated 3/2-way spool valves with FPM/FKM sealings
P... 311 ... VIT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P... 310 ... NT	Pneumatically actuated 3/2-way spool valves for -20°C
P... 311 ... NT	Pneumatically actuated 3/2-way spool valves with mechanical spring return for -20°C
P... 311 ... SR	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch
P... 311 ... SR VIT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch with FPM/FKM sealings
P... 311 ... SR NT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -20°C
P... 311 ... SR 02 NTB	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -25°C
P... 311 ... SR VES	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch, stainless steel
P... 311 ... NTB	Pneumatically actuated 3/2-way spool valves with mechanical spring return for -25°C

Table 5 [V5] Pneumatically operated 4/2-way and 5/2-way valves

Name	Description
P... 411 ... SR	Pneumatically actuated 4/2-way spool valves, with adjustable pneumatic pressure switch
P... 411 ... SR VIT	Pneumatically actuated 4/2-way spool valves, with adjustable pneumatic pressure switch, with FPM/FKM sealings
P... 411 ... SR NT	Pneumatically actuated 4/2-way spool valves, with adjustable pneumatic pressure switch, for -20°C
PN... 411 ... SR	Pneumatically actuated 4/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch
PN... 411 ... SR VIT	Pneumatically actuated 4/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN... 411 ... SR NT	Pneumatically actuated 4/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, for -20°C
P... 510 ...	Pneumatically actuated 5/2-way spool valves
P... 511 ...	Pneumatically actuated 5/2-way spool valves with mechanical spring return
P... 510 ... VES	Pneumatically actuated 5/2-way spool valves, stainless steel
P... 511 ... VES	Pneumatically actuated 5/2-way spool valves with mechanical spring return, stainless steel
P... 510 ... TT	Pneumatically actuated 5/2-way spool valves for low temperature (with unidirectional sealing)
P... 511 ... TT	Pneumatically actuated 5/2-way spool valves with mechanical spring return for low temperature (with unidirectional sealing)

Name	Description
P... 510 ... TT AIR	Pneumatically actuated 5/2-way spool valves for low temperature (with bidirectional sealing)
P... 511 ... TT AIR	Pneumatically actuated 5/2-way spool valves with mechanical spring return, for low temperature (with bidirectional sealing)
P... 510 ... VIT	Pneumatically actuated 5/2-way spool valves, with FPM/FKM sealings
P... 511 ... VIT	Pneumatically actuated 5/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P... 510 ... NT	Pneumatically actuated 5/2-way spool valves for -20°C
P... 511 ... NT	Pneumatically actuated 5/2-way spool valves with mechanical spring return for -20°C
P... 511 ... NTB	Pneumatically actuated 5/2-way spool valves with mechanical spring return for -25°C

Table 6 [V6] Pneumatically operated 5/3-way valves

Name	Description
P... 53. ...	Pneumatically actuated 5/3-way spool valves
P... 53. ... VES	Pneumatically actuated 5/3-way spool valves, stainless steel
P... 53. ... TT	Pneumatically actuated 5/3-way spool valves for low temperature (with unidirectional sealing)
P... 53. ... TT AIR	Pneumatically actuated 5/3-way spool valves for low temperature (with bidirectional sealing)
P... 53. ... VIT	Pneumatically actuated 5/3-way spool valves, with FPM/FKM sealings
P... 53. ... NT	Pneumatically actuated 5/3-way spool valves for -25°C

Table 7 [V7] Pneumatically operated 6/2-way valves

Name	Description
P 611 ... SR	Pneumatically actuated 6/2-way spool valves, with adjustable pneumatic pressure switch
PN 611 ... SR	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch
PN 611 ... SR VIT	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN 611 ... SR NT	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch for -20°C

Table 8 [V8] Pneumatically operated 6/2-way valves type PN 611 121 SR and its versions

Name	Description
PN 611 121 SR	Pneumatically actuated 6/2-way spool valves, G1/2", with Namur interface, with adjustable pneumatic pressure switch
PN 611 121 SR VIT	Pneumatically actuated 6/2-way spool valves, G1/2", with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN 611 121 SR NT	Pneumatically actuated 6/2-way spool valves, G1/2", with Namur interface, with adjustable pneumatic pressure switch for -20°C

Table 9 [V9] Pilot operated 2/2-way solenoid valves

Placeholder “__” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 210 ...	Pilot operated 2/2-way solenoid valves
M... 210 ... VES	Pilot operated 2/2-way solenoid valves, stainless steel
M... 210 ... TT	Pilot operated 2/2-way solenoid valves for low temperature (with unidirectional sealing)
M... 210 ... HT	Pilot operated 2/2-way solenoid valves for high temperature
M... 210 ... NT	Pilot operated 2/2-way solenoid valves for -20°C
M...C 210 ...	Pilot operated 2/2-way solenoid valves with CNOMO interface
M...C 210 ... VES	Pilot operated 2/2-way solenoid valves with CNOMO interface, stainless steel
M...C 210 ... TT	Pilot operated 2/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 210 ... NT	Pilot operated 2/2-way solenoid valves with CNOMO interface, for -20°C
M... 210 ... __ Ex d	Pilot operated 2/2-way solenoid valves with Ex d magnet system
M... 210 ... VES __ Ex d	Pilot operated 2/2-way solenoid valves, stainless steel, with Ex d magnet system
M...C 210 ... TT __ Ex d	Pilot operated 2/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 210 ... NT __ Ex d	Pilot operated 2/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system
M... 211 ...	Pilot operated 2/2-way solenoid valves, with combined spring return
M... 211 ... VES	Pilot operated 2/2-way solenoid valves, with combined spring return, stainless steel
M... 211 ... TT	Pilot operated 2/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)
M... 211 ... HT	Pilot operated 2/2-way solenoid valves, with combined spring return, for high temperature
M... 211 ... NT	Pilot operated 2/2-way solenoid valves, with combined spring return, for -20°C
M...C 211 ...	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return
M...C 211 ... VES	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel
M...C 211 ... TT	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)
M...C 211 ... NT	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C
M... 211 ... __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, with Ex d magnet system
M... 211 ... VES __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system
M...C 211 ... TT __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 211 ... NT __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring

Name	Description
	return, with CNOMO interface, for -20°C, with Ex d magnet system

Table 10 [V10] Pilot operated 3/2-way solenoid valves

Placeholder “_” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 310 ...	Pilot operated 3/2-way solenoid valves
M... 310 ... VES	Pilot operated 3/2-way solenoid valves, stainless steel
M... 310 ... TT	Pilot operated 3/2-way solenoid valves for low temperature (with unidirectional sealing)
M... 310 ... TT AIR	Pilot operated 3/2-way solenoid valves for low temperature (with bidirectional sealing)
M... 310 ... HT	Pilot operated 3/2-way solenoid valves for high temperature
M... 310 ... NT	Pilot operated 3/2-way solenoid valves for -20°C
M...C 310 ...	Pilot operated 3/2-way solenoid valves with CNOMO interface
M...C 310 ... VES	Pilot operated 3/2-way solenoid valves with CNOMO interface, stainless steel
M...C 310 ... TT	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 310 ... TT AIR	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)
M...C 310 ... NT	Pilot operated 3/2-way solenoid valves with CNOMO interface, for -20°C
M... 310 ... _ Ex d	Pilot operated 3/2-way solenoid valves with Ex d magnet system
M... 310 ... VES _ Ex d	Pilot operated 3/2-way solenoid valves, stainless steel, with Ex d magnet system
M...C 310 ... TT _ Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 310 ... TT AIR _ Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 310 ... NT _ Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system
M... 311 ...	Pilot operated 3/2-way solenoid valves, with combined spring return
M... 311 ... VES	Pilot operated 3/2-way solenoid valves, with combined spring return, stainless steel
M... 311 ... TT	Pilot operated 3/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)
M... 311 ... TT AIR	Pilot operated 3/2-way solenoid valves, with combined spring return, for low temperature (with bidirectional sealing)
M... 311 ... HT	Pilot operated 3/2-way solenoid valves, with combined spring return, for high temperature
M... 311 ... NT	Pilot operated 3/2-way solenoid valves, with combined spring return, for -20°C
M... 311 ... NTB	Pilot operated 3/2-way solenoid valves, with combined spring return, for -25°C
M...C 311 ...	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return

Name	Description
M...C 311 ... VES	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel
M...C 311 ... TT	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)
M...C 311 ... TT AIR	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with bidirectional sealing)
M...C 311 ... NT	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C
M... 311 ... __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with Ex d magnet system
M... 311 ... VES __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system
M...C 311 ... TT __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 311 ... TT AIR __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 311 ... NT __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system

Table 11 [V11] Pilot operated 5/2-way solenoid valves

Placeholder “__” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 510 ...	Pilot operated 5/2-way solenoid valves
M... 510 ... VES	Pilot operated 5/2-way solenoid valves, stainless steel
M... 510 ... TT	Pilot operated 5/2-way solenoid valves for low temperature (with unidirectional sealing)
M... 510 ... TT AIR	Pilot operated 5/2-way solenoid valves for low temperature (with bidirectional sealing)
M... 510 ... HT	Pilot operated 5/2-way solenoid valves for high temperature
M... 510 ... NT	Pilot operated 5/2-way solenoid valves for -20°C
M...C 510 ...	Pilot operated 5/2-way solenoid valves with CNOMO interface
M...C 510 ... VES	Pilot operated 5/2-way solenoid valves with CNOMO interface, stainless steel
M...C 510 ... TT	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 510 ... TT AIR	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)
M...C 510 ... NT	Pilot operated 5/2-way solenoid valves with CNOMO interface, for -20°C
M... 510 ... __ Ex d	Pilot operated 5/2-way solenoid valves with Ex d magnet system
M... 510 ... VES __ Ex d	Pilot operated 5/2-way solenoid valves, stainless steel, with Ex d magnet system

Name	Description
M...C 510 ... TT __ Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 510 ... TT AIR __ Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 510 ... NT __ Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system
M... 511 ...	Pilot operated 5/2-way solenoid valves, with combined spring return
M... 511 ... VES	Pilot operated 5/2-way solenoid valves, with combined spring return, stainless steel
M... 511 ... TT	Pilot operated 5/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)
M... 511 ... TT AIR	Pilot operated 5/2-way solenoid valves, with combined spring return, for low temperature (with bidirectional sealing)
M... 511 ... HT	Pilot operated 5/2-way solenoid valves, with combined spring return, for high temperature
M... 511 ... NT	Pilot operated 5/2-way solenoid valves, with combined spring return, for -20°C
M... 511 ... NTB	Pilot operated 5/2-way solenoid valves, with combined spring return, for -25°C
M...C 511 ...	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return
M...C 511 ... VES	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel
M...C 511 ... TT	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)
M...C 511 ... TT AIR	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with bidirectional sealing)
M...C 511 ... NT	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C
M... 511 ... __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with Ex d magnet system
M... 511 ... VES __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system
M...C 511 ... TT __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 511 ... TT AIR __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 511 ... NT __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system

Table 12 [V12] Pilot operated 5/3-way solenoid valves

Placeholder “_” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 53. ...	Pilot operated 5/3-way solenoid valves
M... 53. ... VES	Pilot operated 5/3-way solenoid valves, stainless steel
M... 53. ... TT	Pilot operated 5/3-way solenoid valves for low temperature (with unidirectional sealing)
M... 53. ... TT AIR	Pilot operated 5/3-way solenoid valves for low temperature (with bidirectional sealing)
M... 53. ... HT	Pilot operated 5/3-way solenoid valves for high temperature
M... 53. ... NT	Pilot operated 5/3-way solenoid valves for -20°C
M...C 53. ...	Pilot operated 5/3-way solenoid valves with CNOMO interface
M...C 53. ... VES	Pilot operated 5/3-way solenoid valves with CNOMO interface, stainless steel
M...C 53. ... TT	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 53. ... TT AIR	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)
M...C 53. ... NT	Pilot operated 5/3-way solenoid valves with CNOMO interface, for -20°C
M... 53. ... _ Ex d	Pilot operated 5/3-way solenoid valves with Ex d magnet system
M... 53. ... VES _ Ex d	Pilot operated 5/3-way solenoid valves, stainless steel, with Ex d magnet system
M...C 53. ... TT _ Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 53. ... TT AIR _ Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 53. ... NT _ Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system

Table 13 [V13] Pilot operated 2/2-way solenoid valves with auxiliary control air

Name	Description
MEH 211 ...	Pilot operated 2/2-way solenoid valves with auxiliary control air
MEH 211 ... VES	Pilot operated 2/2-way solenoid valves with auxiliary control air, stainless steel
MEH 211 ... TT	Pilot operated 2/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
MEH 211 ... HT	Pilot operated 2/2-way solenoid valves with auxiliary control air, for high temperature
MEH 211 ... NT	Pilot operated 2/2-way solenoid valves, with auxiliary control air for -20°C

Table 14 [V14] Pilot operated 3/2-way solenoid valves with auxiliary control air

Name	Description
M...EH 311 ...	Pilot operated 3/2-way solenoid valves with auxiliary control air
M...EH 311 ... VES	Pilot operated 3/2-way solenoid valves with auxiliary control air, stainless steel
M...EH 311 ... TT	Pilot operated 3/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
M...EH 311...TT AIR	Pilot operated 3/2-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
M...EH 311 ... HT	Pilot operated 3/2-way solenoid valves with auxiliary control air, for high temperature
M...EH 311 ... NT	Pilot operated 3/2-way solenoid valves, with auxiliary control air for -20°C

Table 15 [V15] Pilot operated 5/2-way solenoid valves with auxiliary control air

Name	Description
M...EH 511 ...	Pilot operated 5/2-way solenoid valves with auxiliary control air
M...EH 511 ... VES	Pilot operated 5/2-way solenoid valves with auxiliary control air, stainless steel
M...EH 511 ... TT	Pilot operated 5/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
M...EH 511 ... TT AIR	Pilot operated 5/2-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
M...EH 511 ... HT	Pilot operated 5/2-way solenoid valves with auxiliary control air, for high temperature
M...EH 511 ... NT	Pilot operated 5/2-way solenoid valves, with auxiliary control air for -20°C

Table 16 [V16] Pilot operated 5/3-way solenoid valves with auxiliary control air

Name	Description
M...EH 53. ...	Pilot operated 5/3-way solenoid valves with auxiliary control air
M...EH 53. ... VES	Pilot operated 5/3-way solenoid valves with auxiliary control air, stainless steel
M...EH 53. ... TT	Pilot operated 5/3-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
M...EH 53. ... TT AIR	Pilot operated 5/3-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
M...EH 53. ... HT	Pilot operated 5/3-way solenoid valves with auxiliary control air, for high temperature
M...EH 53. ... NT	Pilot operated 5/3-way solenoid valves, with auxiliary control air for -20°C

A number of logic-elements, bi-stable and quick-exhaust variants were also subject of the assessment for Systematic Capability. As they share the same development process, verification and testing as the Variants listed above in Tables 1 - 16, the Logic-elements, bi-stable and quick-exhaust variants meet the same requirements for Systematic Capability as the variants. However, these Logic-elements, bi-stable and quick-exhaust variants are not generally suitable for safety applications, so no FMEDA analysis was done for these variants.

2.1 Failure rates

The table below lists the failure rates in FIT (failures / 10⁹ hours) for the variants listed above.

Table 17: Failure rates per IEC 61508:2010

Variant	Profile	<i>exida</i> Profile		
		Failure rates (in FIT)		
		λ_{SD}	λ_{DD}	λ_{DU}
[V1]	5	3	0	377
[V2]	5	3	0	545
[V3]	5	75	0	7
[V4]	5	55	0	330
[V5]	5	55	0	470
[V6]	5	96	0	502
[V7]	5	55	0	540
[V8]	5	111	0	870
[V9]	5	159	0	206
[V10]	5	150	0	230
[V11]	5	150	0	470
[V12]	5	280	0	504
[V13]	5	159	0	280
[V14]	5	145	0	331
[V15]	5	145	0	471
[V16]	5	269	0	504

3 Status of the Document

3.1 Liability

exida prepares reports based on methods advocated in International standards. *exida* accepts no liability whatsoever for the use of this annex or for the correctness of the standards on which the general calculation methods are based.

3.2 Releases

Contract Number	Report Number	Revision Notes
Q23/04-151-C	1511-126-C R003 V3, R1	Naming corrected for M... and P...
Q23/04-151-C	1511-126-C R004 V3, R0	Surveillance audit 2023 New grouping structure implemented.
Q19/02-018-C	1511-126-C R004 V2, R0	Surveillance audit and new versions added: MEH, TT AIR and MH 311
Q15/11-126-C	1511-126-C R004 V1, R0	Review comments implemented
Q15/11-126-C	1511-126-C R004 V0, R1	Draft; Waiting for review

Author: Peter Söderblom


Review: Steven Close V2 R0
Jürgen Hochhaus V3 R0

Release status: Released 09-Jan-2020, V2 R0
24-Jan-2024, V3 R0
30-Jan-2024, V3 R1

3.3 Future Enhancements

At request of client.

3.4 Release Signatures



Peter Söderblom, Senior Safety Engineer



Jürgen Hochhaus, Senior Safety Engineer



IEC 61508 Functional Safety Assessment

Project:

Mechanically actuated valves, direct operated solenoid valves,
pneumatically operated valves and pilot operated solenoid valves

Customer:

HAFNER Pneumatika Kft.
Halászi
Hungary

Contract Number: Q15/11-126-C

Report No.: 15/11-126-C R003

Version V3, Revision R1, January 2024

Peter Söderblom

Management Summary

This report summarizes the results of the functional safety assessment according to IEC 61508 carried out on the following products from HAFNER Pneumatika Kft.:

- Mechanically actuated valves
- Direct operated solenoid valves
- Pneumatically operated valves
- Pilot operated solenoid valves

Hereafter these are referred to as Solenoid valves in this report.

The functional safety assessment performed by *exida* consisted of the following activities:

- *exida* assessed the development process used by HAFNER Pneumatika Kft. through an audit and review of a detailed safety case against the *exida* certification scheme which includes the relevant requirements of IEC 61508. The investigation was executed using subsets of the IEC 61508 requirements tailored to the work scope of the development team.
- *exida* performed a detailed Failure Modes, Effects, and Diagnostic Analysis (FMEDA) analysis of the device documenting the hardware architecture and failure behavior.

The functional safety assessment was performed to the requirements of IEC 61508:2010, SIL3 for mechanical components. A full IEC 61508 Safety Case was prepared using the *exida* Safety Case tool as the primary audit tool. Hardware process requirements and all associated documentation were reviewed. Environmental test reports were reviewed. Also the user documentation (safety manual) was reviewed.

The results of the Functional Safety Assessment can be summarized as:

The audited development process as tailored and implemented by the HAFNER Pneumatika Kft. Solenoid valves development project, complies with the relevant safety management requirements of IEC 61508:2010 SIL3, SC 3 (SIL3 Capable).

The assessment of the FMEDA, done to the requirements of IEC 61508, has shown that the Solenoid valves can be used in a low demand safety related system in a manor where the PFD_{avg} is within the allowed range for up to SIL2 (HFT = 0) according to table 3 of IEC 61508-1.

The assessment of the FMEDA also shows that the Solenoid valves meet requirements for architectural constraints of an element such that it can be used to implement a SIL 2 safety function (with HFT = 0) or a SIL 3 safety function (with HFT = 1).

This means that the Solenoid valves are capable for use in SIL3 applications in Low DEMAND mode, when properly designed into a Safety Instrumented Function per the requirements in the Safety Manual and when using the versions specified in section 3.1 of this document.



The manufacturer will be entitled to use the Functional Safety Logo.



Table of Contents

Management Summary	2
1 Purpose and Scope	6
1.1 Tools and Methods used for the assessment	6
2 Project Management.....	7
2.1 <i>exida</i>	7
2.2 Roles of the parties involved	7
2.3 Standards and literature used	7
2.4 Reference documents	7
2.4.1 Documentation provided by HAFNER Pneumatika Kft.....	7
2.4.2 Documentation generated by <i>exida</i>	12
2.5 Assessment Approach	13
3 Product Description	14
3.1 Hardware Version Numbers	24
4 IEC 61508 Functional Safety Assessment Scheme.....	25
4.1 Methodology	25
4.2 Assessment level	25
5 Results of the IEC 61508 Functional Safety Assessment.....	26
5.1 Lifecycle Activities and Fault Avoidance Measures	26
5.1.1 Functional Safety Management	26
5.1.2 Safety Requirements Specification and Architecture Design.....	27
5.1.3 Hardware Design.....	27
5.1.4 Validation.....	27
5.1.5 Verification.....	27
5.1.6 Modifications	27
5.1.7 User documentation.....	28
5.2 Hardware Assessment.....	28
5.2.1 Failure rates	29
6 IEC 61508 Functional Safety Surveillance Audit	30
6.1 Roles of the parties involved	30
6.2 Surveillance Methodology	30
6.3 Surveillance Results 2019.....	31
6.3.1 Procedure Changes.....	31
6.3.2 Engineering Changes	31
6.3.3 Impact Analysis	31
6.3.4 Field History	31
6.3.5 Safety Manual.....	31
6.3.6 FMEDA Update	31
6.3.7 Evaluate use of certificate and/or certification mark	31
6.3.8 Previous Recommendations.....	31
6.4 Surveillance Results 2023.....	32
6.4.1 Procedure Changes.....	32



6.4.2	Engineering Changes	32
6.4.3	Impact Analysis	32
6.4.4	Field History	32
6.4.5	Safety Manual.....	32
6.4.6	FMEDA Update	32
6.4.7	Evaluate use of certificate and/or certification mark	32
6.4.8	Previous Recommendations	32
6.4.9	Surveillance Audit Conclusion	32
7	Terms and Definitions	34
8	Status of the Document	35
8.1	Liability	35
8.2	Releases	35
8.3	Future Enhancements	35
8.4	Release Signatures	35

1 Purpose and Scope

This document shall describe the results of the IEC 61508 functional safety assessment of the following products from HAFNER Pneumatika Kft.:

- Mechanically actuated valves
- Direct operated solenoid valves
- Pneumatically operated valves
- Pilot operated solenoid valves

by *exida* according to accredited *exida* certification scheme which includes the requirements of IEC 61508:2010.

The assessment has been carried out based on the quality procedures and scope definitions of *exida*.

The results of this provide the safety instrumentation engineer with the required failure data as per IEC 61508 / IEC 61511 and confidence that sufficient attention has been given to systematic failures during the development process of the device.

1.1 Tools and Methods used for the assessment

This assessment was carried by using the *exida* Safety Case tool. The Safety Case tool contains the *exida* scheme which includes all the relevant requirements of IEC 61508.

For the fulfillment of the objectives, expectations are defined which builds the acceptance level for the assessment. The expectations are reviewed to verify that each single requirement is covered. Because of this methodology, comparable assessments in multiple projects with different assessors are achieved. The arguments for the positive judgment of the assessor are documented within this tool and summarized within this report.

The assessment was planned by *exida* agreed with HAFNER Pneumatika Kft..

All assessment steps were continuously documented by *exida* (see [R1] - [R7]).

2 Project Management

2.1 *exida*

exida is one of the world's leading accredited Certification Bodies and knowledge companies specializing in automation system safety and availability with over 300 years of cumulative experience in functional safety. Founded by several of the world's top reliability and safety experts from assessment organizations and manufacturers, *exida* is a global company with offices around the world. *exida* offers training, coaching, project oriented system consulting services, safety lifecycle engineering tools, detailed product assurance, cyber-security and functional safety certification, and a collection of on-line safety and reliability resources. *exida* maintains a comprehensive failure rate and failure mode database on process equipment.

2.2 Roles of the parties involved

HAFNER Pneumatika Kft. Manufacturer of the Solenoid valves

exida Performed the hardware assessment

exida Performed the IEC 61508 Functional Safety Assessment.

HAFNER contracted *exida* in April 2016 for the IEC 61508 Functional Safety Assessment of the above mentioned device. The development audit was performed in Halászi, June 6 – 8 2016.

2.3 Standards and literature used

The services delivered by *exida* were performed based on the following standards / literature.

[N1]	IEC 61508 (Parts 1 - 3): 2010	Functional Safety of Electrical/Electronic/Programmable Electronic Safety-Related Systems
------	-------------------------------	---

2.4 Reference documents

Note: Documents revised for the 2020 surveillance audit are marked with * below. The ones updated for the 2023 Surveillance audit are marked with **.

2.4.1 Documentation provided by HAFNER Pneumatika Kft.

[D1]	Original filenames in Hungarian, please see Original Names.png.	MK Quality manual
[D2]		ME-T3 Project management
[D3]		FE-01-0001 Internal documentation registry
[D4]		ME-01 Documentation management
[D5]		ME-T7 Reclamation management
[D6]		FE-T7-0007 Reclamation report
[D7]		Fe-T7-0001 D8 report
[D8]		ME-F3 Purchasing process
[D9]		FE-F3-0002 Supplier selection data sheet
[D10]		ME-01 Documentation management
[D11]		ME-T3 Project management

[D12]		ME-01 Documentation management
[D13]		LU-T6-000 General test procedures
[D14]		FE-T9-0007 Competence and responsibility matrix for the design department
[D15]		FE-T9-0009 Training plan
[D16]		FE-T9-0005 Training program
[D17]		*ISO 9001:2015 certificate; N QMS-38784/h
[D18]		FE-T3-0000 Customer request data sheet
[D19]		FE-T3-0001 Feasibility checklist
[D20]		Verification results: MH 311 704 Ex m
[D21]		LU-T6-000 General test procedures
[D22]		MN-54-01 Test report
[D23]		ERP system: P@rtner.erp V3.1. (Screenshot)
[D24]		User manual; BTA-Namurflex
[D25]		Safety manual V1 R1 of September 2016
[D26]	BR 311 301 VES.pdf	Mechanical drawing BR 311 301 VES of 2016.06.13
[D27]	BR 311 301.pdf	Mechanical drawing BR 311 301 of 2014.07.08
[D28]	BR 511 301 VES.pdf	Mechanical drawing BR 511 301 VES of 2016.07.06
[D29]	BR 511 301.pdf	Mechanical drawing BR 511 301 of 2014.03.31
[D30]	M 311 704 VES Ex m.pdf	Mechanical drawing M 311 704 VES Ex m of 2016.05.31
[D31]	M 504 VES 01 EXM.pdf	Mechanical drawing M 504 VES 01 EXM of 2016.05.31
[D32]	MH 210 701 TT.pdf	Mechanical drawing MH 210 701 TT of 2014.05.22
[D33]	MH 210 701 VES.pdf	Mechanical drawing MH 210 701 VES of 2016.07.06
[D34]	MH 210 701.pdf	Mechanical drawing MH 210 701 of 2012.10.24
[D35]	MH 211 015 VES.pdf	Mechanical drawing MH 211 015 VES of 2016.07.06
[D36]	MH 211 015.pdf	Mechanical drawing MH 211 015 of 2014.04.10
[D37]	MH 211 701 TT.pdf	Mechanical drawing MH 211 701 TT of 2016.07.06
[D38]	MH 211 701 VES.pdf	Mechanical drawing MH 211 701 VES of 2016.07.06
[D39]	MH 211 701.pdf	Mechanical drawing MH 211 701 of 2014.09.29
[D40]	MH 310 701 TT.pdf	Mechanical drawing MH 310 701 TT of 2013.10.04
[D41]	MH 310 701 VES.pdf	Mechanical drawing MH 310 701 VES of 2013.09.19
[D42]	MH 310 701.pdf	Mechanical drawing MH 310 701 of 2013.02.18
[D43]	MH 311 015 TT.pdf	Mechanical drawing MH 311 015 TT of 2013.08.28
[D44]	MH 311 015 VES.pdf	Mechanical drawing MH 311 015 VES of 2013.10.02
[D45]	MH 311 015.pdf	Mechanical drawing MH 311 015 of 2013.01.16
[D46]	MH 311 701 TT.pdf	Mechanical drawing MH 311 701 TT of 2013.03.06

[D47]	MH 311 701 VES.pdf	Mechanical drawing MH 311 701 VES of 2013.09.24
[D48]	MH 311 701.pdf	Mechanical drawing MH 311 701 of 2012.08.17
[D49]	MH 311 704 VES Ex m.pdf	Mechanical drawing MH 311 704 VES Ex m of 2016.04.01
[D50]	MH 320 704 VES Ex m.pdf	Mechanical drawing MH 320 704 VES Ex m of 2016.04.01
[D51]	MH 501 TT.pdf	Mechanical drawing MH 501 TT of 2013.09.13
[D52]	MH 501 VES.pdf	Mechanical drawing MH 501 VES of 2013.07.02
[D53]	MH 501.pdf	Mechanical drawing MH 501 of 2012.12.17
[D54]	MH 504 VES 01 EXM.pdf	Mechanical drawing MH 504 VES 01 EXM of 2016.04.01
[D55]	MH 510 701 TT.pdf	Mechanical drawing MH 510 701 TT of 2012.06.29
[D56]	MH 510 701 VES.pdf	Mechanical drawing MH 510 701 VES of 2013.04.30
[D57]	MH 510 701.pdf	Mechanical drawing MH 510 701 of 2013.02.12
[D58]	MH 511 701 TT.pdf	Mechanical drawing MH 511 701 TT of 2016.05.30
[D59]	MH 511 701 VES.pdf	Mechanical drawing MH 511 701 VES of 2013.09.18
[D60]	MH 511 701.pdf	Mechanical drawing MH 511 701 of 2014.01.10
[D61]	MH 531 701 TT.pdf	Mechanical drawing MH 531 701 TT of 2013.09.26
[D62]	MH 531 701 VES.pdf	Mechanical drawing MH 531 701 VES of 2013.09.18
[D63]	MH 531 701.pdf	Mechanical drawing MH 531 701 of 2012.11.09
[D64]	P 310 701 TT.pdf	Mechanical drawing P 310 701 TT of 2016.07.06
[D65]	P 310 701 VES.pdf	Mechanical drawing P 310 701 VES of 2013.02.25
[D66]	P 310 701.pdf	Mechanical drawing P 310 701 of 2014.01.17
[D67]	P 311 701 TT.pdf	Mechanical drawing P 311 701 TT of 2016.07.06
[D68]	P 311 701 VES.pdf	Mechanical drawing P 311 701 VES of 2013.02.25
[D69]	P 311 701.pdf	Mechanical drawing P 311 701 of 2014.11.28
[D70]	P 501 01 VES.pdf	Mechanical drawing P 501 01 VES of 2013.02.26
[D71]	P 501 01.pdf	Mechanical drawing P 501 01 of 2012.12.18
[D72]	P 501 02.pdf	Mechanical drawing P 501 02 of 2012.12.18
[D73]	P 510 701 TT.pdf	Mechanical drawing P 510 701 TT of 2014.05.22
[D74]	P 510 701 VES.pdf	Mechanical drawing P 510 701 VES of 2013.09.18
[D75]	P 510 701.pdf	Mechanical drawing P 510 701 of 2012.12.12
[D76]	P 511 701 TT.pdf	Mechanical drawing P 511 701 TT of 2016.07.06
[D77]	P 511 701 VES.pdf	Mechanical drawing P 511 701 VES of 2013.09.19
[D78]	P 511 701.pdf	Mechanical drawing P 511 701 of 2013.01.17
[D79]	P 531 701 TT.pdf	Mechanical drawing P 531 701 TT of 2016.07.06
[D80]	P 531 701 VES.pdf	Mechanical drawing P 531 701 VES of 2013.09.18

[D81]	P 531 701.pdf	Mechanical drawing P 531 701 of 2013.02.25
[D82]	MH 532 701 TT.pdf	Mechanical drawing MH 532 701 TT of 2016.08.11
[D83]	MH 532 701 VES.pdf	Mechanical drawing MH 532 701 VES of 2013.09.18
[D84]	MH 532 701.pdf	Mechanical drawing MH 532 701 of 2013.01.14
[D85]	MH 533 701 TT.pdf	Mechanical drawing MH 533 701 TT of 2016.08.11
[D86]	MH 533 701 VES.pdf	Mechanical drawing MH 533 701 VES of 2013.09.18
[D87]	MH 533 701.pdf	Mechanical drawing MH 533 701 of 2013.02.19
[D88]	P 532 701 TT.pdf	Mechanical drawing P 532 701 TT of 2016.08.11
[D89]	P 532 701 VES.pdf	Mechanical drawing P 532 701 VES of 2013.09.18
[D90]	P 532 701.pdf	Mechanical drawing P 532 701 of 2013.02.25
[D91]	P 533 701 TT.pdf	Mechanical drawing P 533 701 TT of 2015.11.11
[D92]	P 533 701 VES.pdf	Mechanical drawing P 533 701 VES of 2013.09.18
[D93]	P 533 701.pdf	Mechanical drawing P 533 701 of 2013.02.25
[D94]	MNH 350 701.pdf	Mechanical drawing MNH 350 701 of 2013.03.04
[D95]	MNH 351 701.pdf	Mechanical drawing MNH 351 701 of 2012.10.15
[D96]	MH 310 121 TT AIR.pdf	Mechanical drawing MH 310 121 TT AIR of 23.11.2018
[D97]	MH 311 701 TT AIR.pdf	Mechanical drawing MH 311 701 TT AIR of 23.11.2018
[D98]	MH 510 121 TT AIR.pdf	Mechanical drawing MH 510 121 TT AIR of 24.10.2018
[D99]	MH 511 701 TT AIR.pdf	Mechanical drawing MH 511 701 TT AIR of 14.09.2017
[D100]	MH 531 701 TT AIR.pdf	Mechanical drawing MH 531 701 TT AIR of 18.09.2017
[D101]	MH 532 701 TT AIR.pdf	Mechanical drawing MH 532 701 TT AIR of 23.11.2018
[D102]	MH 533 701 TT AIR.pdf	Mechanical drawing MH 533 701 TT AIR of 23.11.2018
[D103]	P 310 121 TT AIR.pdf	Mechanical drawing P 310 121 TT AIR of 23.11.2018
[D104]	P 311 701 TT AIR.pdf	Mechanical drawing P 311 701 TT AIR of 23.11.2018
[D105]	P 510 121 TT AIR.pdf	Mechanical drawing P 510 121 TT AIR of 23.11.2018
[D106]	P 511 701 TT AIR.pdf	Mechanical drawing P 511 701 TT AIR of 23.11.2018
[D107]	P 531 701 TT AIR.pdf	Mechanical drawing P 531 701 TT AIR of 23.11.2018
[D108]	P 532 701 TT AIR.pdf	Mechanical drawing P 532 701 TT AIR of 23.11.2018
[D109]	P 533 701 TT AIR.pdf	Mechanical drawing P 533 701 TT AIR of 23.11.2018
[D110]	MEH 211 701 TT.pdf	Mechanical drawing MEH 211 701 TT of 26.11.2018
[D111]	MEH 211 701 VES.pdf	Mechanical drawing MEH 211 701 VES of 26.11.2018
[D112]	MEH 211 701.pdf	Mechanical drawing MEH 211 701 of 26.11.2018
[D113]	MEH 311 701 TT AIR.pdf	Mechanical drawing MEH 311 701 TT AIR of 26.11.2018
[D114]	MEH 311 701 TT.pdf	Mechanical drawing MEH 311 701 TT of 26.11.2018
[D115]	MEH 311 701 VES.pdf	Mechanical drawing MEH 311 701 VES of 26.11.2018

[D116]	MEH 311 701.pdf	Mechanical drawing MEH 311 701 of 19.02.2013
[D117]	MEH 511 701 TT AIR.pdf	Mechanical drawing MEH 511 701 TT AIR of 26.11.2018
[D118]	MEH 511 701 TT.pdf	Mechanical drawing MEH 511 701 TT of 23.01.2013
[D119]	MEH 511 701 VES.pdf	Mechanical drawing MEH 511 701 VES of 26.11.2018
[D120]	MEH 511 701.pdf	Mechanical drawing MEH 511 701 of 23.01.2013
[D121]	MEH 531 701 TT AIR.pdf	Mechanical drawing MEH 531 701 TT AIR of 26.11.2018
[D122]	MEH 531 701 TT.pdf	Mechanical drawing MEH 531 701 TT of 26.11.2018
[D123]	MEH 531 701 VES.pdf	Mechanical drawing MEH 531 701 VES of 26.11.2018
[D124]	MEH 531 701.pdf	Mechanical drawing MEH 531 701 of 08.11.2013
[D125]	MEH 532 701 TT AIR.pdf	Mechanical drawing MEH 532 701 TT AIR of 26.11.2018
[D126]	MEH 532 701 TT.pdf	Mechanical drawing MEH 532 701 TT of 26.11.2018
[D127]	MEH 532 701 VES.pdf	Mechanical drawing MEH 532 701 VES of 26.11.2018
[D128]	MEH 532 701.pdf	Mechanical drawing MEH 532 701 of 26.11.2018
[D129]	MEH 533 701 TT AIR.pdf	Mechanical drawing MEH 533 701 TT AIR of 26.11.2018
[D130]	MEH 533 701 TT.pdf	Mechanical drawing MEH 533 701 TT of 26.11.2018
[D131]	MEH 533 701 VES.pdf	Mechanical drawing MEH 533 701 VES of 26.11.2018
[D132]	MEH 533 701.pdf	Mechanical drawing MEH 533 701 of 26.11.2018
[D133]	MEH 501 TT.pdf	Mechanical drawing MEH 501 TT of 26.11.2018
[D134]	MEH 501 VES.pdf	Mechanical drawing MEH 501 VES of 03.02.2017
[D135]	MEH 501.pdf	Mechanical drawing MEH 501 of 15.02.2013
[D136]	MH 121 TT.pdf	Mechanical drawing MH 121 TT of 06.09.2013
[D137]	MH 501 TT.pdf	Mechanical drawing MH 501 TT of 13.09.2013
[D138]	P 121 01.pdf	Mechanical drawing P 121 01 of 18.12.2012
[D139]	ZD MH 501 TT AIR.pdf	Mechanical drawing ZD MH 501 TT AIR of 24.08.2017
[D140]	ZD MH 530 TT AIR.pdf	Mechanical drawing ZD MH 530 TT AIR of 23.11.2017
[D141]	HAFNER Ventilgruppen - 2018.11.23..xlsx	
[D142]	**SIL EXIDA 2023.zip	New drawings of 3.04.2023
[D143]	* MH 311 209 - 24DC - FE-T3-0001.pdf	Development order close for MH 311 209 - 24DC of 2016-05-24
[D144]	* MH 311 209 - 24DC - FE-T3-0004.pdf	Verification report for MH 311 209 - 24DC of 2016-05-24
[D145]	* MH 510 121 TT AIR - FE-T3-0001.pdf	Development order close for MH 510 121 TT AIR of 2017-05-12
[D146]	* MH 510 121 TT AIR - FE-T3-0004.pdf	Verification report for MH 510 121 TT AIR of 2017-05-12
[D147]	* Testbericht MH 520 701 TT AIR-24DC_20170526	Test report MH 510 121 TT AR – 24 VDC

[D148]	*Nr. 649 - 20161103 - REKLAMATIONSBERIC HT.pdf	Field return report
[D149]	*Nr. 677 - 20170503 - REKLAMATIONSBERIC HT.pdf	Field return report
[D150]	*Nr. 689 - 20170705 - REKLAMATIONSBERIC HT.pdf	Field return report
[D151]	*SIL 3 Field returns of functional faults 2016-2019.xls	Field returns 2016 – 2019
[D152]	HAFNER Valves 2023.pdf	Product catalogue

2.4.2 Documentation generated by *exida*

[R1]	*HAFNER 1511-126-C Hardware process V2 R0.docx	Assessment and review comments
[R2]	*HAFNER 1511-126-C R002 Safety case.xls	IEC 61508 SafetyCaseDB for Solenoid valves
[R3]	* Hafner 1511-126-C R003 Assessment Report Solenoid valves V3R1.docx	IEC 61508 Functional Safety Assessment, HAFNER Pneumatika Kft. Solenoid valves (this report)
[R4]	** HAFNER 15-11-126-C R001 V3R2.pdf	FMEDA report HAFNER Solenoid valves
[R5]	* HAFNER 1511-126-C R004 Assessment recommendations V1R1.pdf	Recommendations from the assessment (confidential document)
[R6]	** HAFNER 1511-126-C Annex to certificate R004 V3 R0.	Certificate annex.
[R7]	**Hafner 2304-151-C R001 Assessment and Review comments V1R0	Assessment and review comments for the 2023 audit.
[R8]	**HAFNER 2304-151-C R002 FFA V1R0	Field failure analysis 2023

2.5 Assessment Approach

The certification audit was closely driven by requirements of the *exida* scheme which includes subsets filtered from IEC 61508.

The assessment was planned by *exida* and agreed upon by HAFNER Pneumatika Kft..

The following IEC 61508 objectives were subject to detailed auditing at HAFNER Pneumatika Kft.:

- FSM planning, including
 - Safety Life Cycle definition
 - Scope of the FSM activities
 - Documentation
 - Activities and Responsibilities (Training and competence)
 - Configuration management
 - Tools
- Safety Requirement Specification
- Change and modification management
- Hardware architecture design - process, techniques and documentation
- Hardware design / probabilistic modeling
- Hardware and system related V&V activities including documentation, verification
 - Fault insertion test strategy
- System / hardware validation
- Hardware-related operation, installation and maintenance requirements

3 Product Description

The mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves can be considered to be part of a Type A element with a hardware fault tolerance of 0.

Tables 1 - 16 gives an overview of the different variants that belong to the considered mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves.

For safety applications only the described variants in Tables 1 - 16 of the mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves working as DTT (De-energize To Trip) devices have been considered.

For more information regarding the assessed variants, see [D152]

Table 1: [V1] Mechanically actuated 3/2-way valves

Name	Description
BR 311 ...	Mechanically actuated 3/2-way roller lever valves
BR 311 ... VES	Mechanically actuated 3/2-way roller lever valves, stainless steel
BV 311 ...	Mechanically actuated 3/2-way stem valves
BV 311 ... VES	Mechanically actuated 3/2-way stem valves, stainless steel
BV 311 ... TT	Mechanically actuated 3/2-way stem valves for low temperature (with unidirectional sealing)
BL 311 ...	Mechanically actuated 3/2-way roller lever valves with idle return
BG 311 ...	Mechanically actuated 3/2-way stem actuated spool valves
BG 311 ... TT	Mechanically actuated 3/2-way stem actuated spool valves for low temperature (with unidirectional sealing)
BG 311 ... TT AIR	Mechanically actuated 3/2-way stem actuated spool valves for low temperature (with bidirectional sealing)

Table 2 [V2] Mechanically actuated 5/2-way valves

Name	Description
BR 511 ...	Mechanically actuated 5/2-way roller lever valves
BR 511 ... VES	Mechanically actuated 5/2-way roller lever valves, stainless steel
BV 511 ...	Mechanically actuated 5/2-way stem valves
BV 511 ... VES	Mechanically actuated 5/2-way stem valves, stainless steel
BV 311 ... TT	Mechanically actuated 3/2-way stem valves for low temperature (with unidirectional sealing)
BL 511 ...	Mechanically actuated 5/2-way roller lever valves with idle return

Table 3 [V3] Direct operated 2/2-way and 3/2-way solenoid valves

Name	Description
M... 211 ...	Direct actuated in-line 2/2-way solenoid valves
M... 211 ... VES	Direct actuated in-line 2/2-way solenoid valves, stainless steel
M... 311 ...	Direct actuated in-line 3/2-way solenoid valves
M...311 ... VES	Direct actuated in-line 3/2-way solenoid valves, stainless steel
M... 311 ... TT	Direct actuated in-line 3/2-way solenoid valves for low temperature (with unidirectional sealing)

Table 4 [V4] Pneumatically operated 2/2-way and 3/2-way valves

Name	Description
P... 210 ...	Pneumatically actuated 2/2-way spool valves
P... 211 ...	Pneumatically actuated 2/2-way spool valves with mechanical spring return
P... 210 ... VES	Pneumatically actuated 2/2-way spool valves, stainless steel
P... 211 ... VES	Pneumatically actuated 2/2-way spool valves with mechanical spring return stainless steel
P... 210 ... TT	Pneumatically actuated 2/2-way spool valves for low temperature (with unidirectional sealing)
P... 211 ... TT	Pneumatically actuated 2/2-way spool valves with mechanical spring return (with unidirectional sealing)
P... 210 ... VIT	Pneumatically actuated 2/2-way spool valves with FPM/FKM sealings
P... 211 ... VIT	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P... 210 ... NT	Pneumatically actuated 2/2-way spool valves for -20°C
P... 211 ... NT	Pneumatically actuated 2/2-way spool valves with mechanical spring return for -20°C
P... 211 ... SR	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch
P... 211 ... SR VIT	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch with FPM/FKM sealings
P... 211 ... SR NT	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -20°C
P... 211 ... SR 02 NTB	Pneumatically actuated 2/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -25°C
P... 310 ...	Pneumatically actuated 3/2-way spool valves
P... 311 ...	Pneumatically actuated 3/2-way spool valves with mechanical spring return
P... 310 ... VES	Pneumatically actuated 3/2-way spool valves, stainless steel
P... 311 ... VES	Pneumatically actuated 3/2-way spool valves with mechanical spring return stainless steel
P... 310 ... TT	Pneumatically actuated 3/2-way spool valves for low temperature (with unidirectional sealing)
P... 311 ... TT	Pneumatically actuated 3/2-way spool valves with mechanical spring return (with unidirectional sealing)
P... 310 ... TT AIR	Pneumatically actuated 3/2-way spool valves for low temperature (with bidirectional sealing)
P... 311 ... TT AIR	Pneumatically actuated 3/2-way spool valves with mechanical spring return (with bidirectional sealing)
P... 310 ... VIT	Pneumatically actuated 3/2-way spool valves with FPM/FKM sealings
P... 311 ... VIT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P... 310 ... NT	Pneumatically actuated 3/2-way spool valves for -20°C
P... 311 ... NT	Pneumatically actuated 3/2-way spool valves with mechanical spring return for -20°C
P... 311 ... SR	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch

Name	Description
P... 311 ... SR VIT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch with FPM/FKM sealings
P... 311 ... SR NT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -20°C
P... 311 ... SR 02 NTB	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for -25°C
P... 311 ... SR VES	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch, stainless steel
P... 311 ... NTB	Pneumatically actuated 3/2-way spool valves with mechanical spring return for -25°C

Table 5 [V5] Pneumatically operated 4/2-way and 5/2-way valves

Name	Description
P... 411 ... SR	Pneumatically actuated 4/2-way spool valves, with adjustable pneumatic pressure switch
P... 411 ... SR VIT	Pneumatically actuated 4/2-way spool valves, with adjustable pneumatic pressure switch, with FPM/FKM sealings
P... 411 ... SR NT	Pneumatically actuated 4/2-way spool valves, with adjustable pneumatic pressure switch, for -20°C
PN... 411 ... SR	Pneumatically actuated 4/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch
PN... 411 ... SR VIT	Pneumatically actuated 4/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN... 411 ... SR NT	Pneumatically actuated 4/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, for -20°C
P... 510 ...	Pneumatically actuated 5/2-way spool valves
P... 511 ...	Pneumatically actuated 5/2-way spool valves with mechanical spring return
P... 510 ... VES	Pneumatically actuated 5/2-way spool valves, stainless steel
P... 511 ... VES	Pneumatically actuated 5/2-way spool valves with mechanical spring return, stainless steel
P... 510 ... TT	Pneumatically actuated 5/2-way spool valves for low temperature (with unidirectional sealing)
P... 511 ... TT	Pneumatically actuated 5/2-way spool valves with mechanical spring return for low temperature (with unidirectional sealing)
P... 510 ... TT AIR	Pneumatically actuated 5/2-way spool valves for low temperature (with bidirectional sealing)
P... 511 ... TT AIR	Pneumatically actuated 5/2-way spool valves with mechanical spring return, for low temperature (with bidirectional sealing)
P... 510 ... VIT	Pneumatically actuated 5/2-way spool valves, with FPM/FKM sealings
P... 511 ... VIT	Pneumatically actuated 5/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P... 510 ... NT	Pneumatically actuated 5/2-way spool valves for -20°C
P... 511 ... NT	Pneumatically actuated 5/2-way spool valves with mechanical spring return for -20°C

Name	Description
P... 511 ... NTB	Pneumatically actuated 5/2-way spool valves with mechanical spring return for -25°C

Table 6 [V6] Pneumatically operated 5/3-way valves

Name	Description
P... 53. ...	Pneumatically actuated 5/3-way spool valves
P... 53. ... VES	Pneumatically actuated 5/3-way spool valves, stainless steel
P... 53. ... TT	Pneumatically actuated 5/3-way spool valves for low temperature (with unidirectional sealing)
P... 53. ... TT AIR	Pneumatically actuated 5/3-way spool valves for low temperature (with bidirectional sealing)
P... 53. ... VIT	Pneumatically actuated 5/3-way spool valves, with FPM/FKM sealings
P... 53. ... NT	Pneumatically actuated 5/3-way spool valves for -25°C

Table 7 [V7] Pneumatically operated 6/2-way valves

Name	Description
P 611 ... SR	Pneumatically actuated 6/2-way spool valves, with adjustable pneumatic pressure switch
PN 611 ... SR	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch
PN 611 ... SR VIT	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN 611 ... SR NT	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch for -20°C

Table 8 [V8] Pneumatically operated 6/2-way valves type PN 611 121 SR and its versions

Name	Description
PN 611 121 SR	Pneumatically actuated 6/2-way spool valves, G1/2", with Namur interface, with adjustable pneumatic pressure switch
PN 611 121 SR VIT	Pneumatically actuated 6/2-way spool valves, G1/2", with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN 611 121 SR NT	Pneumatically actuated 6/2-way spool valves, G1/2", with Namur interface, with adjustable pneumatic pressure switch for -20°C

Table 9 [V9] Pilot operated 2/2-way solenoid valves

Placeholder “_” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 210 ...	Pilot operated 2/2-way solenoid valves
M... 210 ... VES	Pilot operated 2/2-way solenoid valves, stainless steel
M... 210 ... TT	Pilot operated 2/2-way solenoid valves for low temperature (with unidirectional sealing)
M... 210 ... HT	Pilot operated 2/2-way solenoid valves for high temperature
M... 210 ... NT	Pilot operated 2/2-way solenoid valves for -20°C

Name	Description
M...C 210 ...	Pilot operated 2/2-way solenoid valves with CNOMO interface
M...C 210 ... VES	Pilot operated 2/2-way solenoid valves with CNOMO interface, stainless steel
M...C 210 ... TT	Pilot operated 2/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 210 ... NT	Pilot operated 2/2-way solenoid valves with CNOMO interface, for -20°C
M... 210 ... __ Ex d	Pilot operated 2/2-way solenoid valves with Ex d magnet system
M... 210 ... VES __ Ex d	Pilot operated 2/2-way solenoid valves, stainless steel, with Ex d magnet system
M...C 210 ... TT __ Ex d	Pilot operated 2/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 210 ... NT __ Ex d	Pilot operated 2/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system
M... 211 ...	Pilot operated 2/2-way solenoid valves, with combined spring return
M... 211 ... VES	Pilot operated 2/2-way solenoid valves, with combined spring return, stainless steel
M... 211 ... TT	Pilot operated 2/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)
M... 211 ... HT	Pilot operated 2/2-way solenoid valves, with combined spring return, for high temperature
M... 211 ... NT	Pilot operated 2/2-way solenoid valves, with combined spring return, for -20°C
M...C 211 ...	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return
M...C 211 ... VES	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel
M...C 211 ... TT	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)
M...C 211 ... NT	Pilot operated 2/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C
M... 211 ... __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, with Ex d magnet system
M... 211 ... VES __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system
M...C 211 ... TT __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 211 ... NT __ Ex d	Pilot operated 2/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system

Table 10 [V10] Pilot operated 3/2-way solenoid valves

Placeholder “__” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 310 ...	Pilot operated 3/2-way solenoid valves
M... 310 ... VES	Pilot operated 3/2-way solenoid valves, stainless steel
M... 310 ... TT	Pilot operated 3/2-way solenoid valves for low temperature (with unidirectional sealing)
M... 310 ... TT AIR	Pilot operated 3/2-way solenoid valves for low temperature (with bidirectional sealing)
M... 310 ... HT	Pilot operated 3/2-way solenoid valves for high temperature
M... 310 ... NT	Pilot operated 3/2-way solenoid valves for -20°C
M...C 310 ...	Pilot operated 3/2-way solenoid valves with CNOMO interface
M...C 310 ... VES	Pilot operated 3/2-way solenoid valves with CNOMO interface, stainless steel
M...C 310 ... TT	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 310 ... TT AIR	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)
M...C 310 ... NT	Pilot operated 3/2-way solenoid valves with CNOMO interface, for -20°C
M... 310 ... __ Ex d	Pilot operated 3/2-way solenoid valves with Ex d magnet system
M... 310 ... VES __ Ex d	Pilot operated 3/2-way solenoid valves, stainless steel, with Ex d magnet system
M...C 310 ... TT __ Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 310 ... TT AIR __ Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 310 ... NT __ Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system
M... 311 ...	Pilot operated 3/2-way solenoid valves, with combined spring return
M... 311 ... VES	Pilot operated 3/2-way solenoid valves, with combined spring return, stainless steel
M... 311 ... TT	Pilot operated 3/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)
M... 311 ... TT AIR	Pilot operated 3/2-way solenoid valves, with combined spring return, for low temperature (with bidirectional sealing)
M... 311 ... HT	Pilot operated 3/2-way solenoid valves, with combined spring return, for high temperature
M... 311 ... NT	Pilot operated 3/2-way solenoid valves, with combined spring return, for -20°C
M... 311 ... NTB	Pilot operated 3/2-way solenoid valves, with combined spring return, for -25°C
M...C 311 ...	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return
M...C 311 ... VES	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel

Name	Description
M...C 311 ... TT	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)
M...C 311 ... TT AIR	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with bidirectional sealing)
M...C 311 ... NT	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C
M... 311 ... __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with Ex d magnet system
M... 311 ... VES __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system
M...C 311 ... TT __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 311 ... TT AIR __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 311 ... NT __ Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system

Table 11 [V11] Pilot operated 5/2-way solenoid valves

Placeholder “__” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 510 ...	Pilot operated 5/2-way solenoid valves
M... 510 ... VES	Pilot operated 5/2-way solenoid valves, stainless steel
M... 510 ... TT	Pilot operated 5/2-way solenoid valves for low temperature (with unidirectional sealing)
M... 510 ... TT AIR	Pilot operated 5/2-way solenoid valves for low temperature (with bidirectional sealing)
M... 510 ... HT	Pilot operated 5/2-way solenoid valves for high temperature
M... 510 ... NT	Pilot operated 5/2-way solenoid valves for -20°C
M...C 510 ...	Pilot operated 5/2-way solenoid valves with CNOMO interface
M...C 510 ... VES	Pilot operated 5/2-way solenoid valves with CNOMO interface, stainless steel
M...C 510 ... TT	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 510 ... TT AIR	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)
M...C 510 ... NT	Pilot operated 5/2-way solenoid valves with CNOMO interface, for -20°C
M... 510 ... __ Ex d	Pilot operated 5/2-way solenoid valves with Ex d magnet system
M... 510 ... VES __ Ex d	Pilot operated 5/2-way solenoid valves, stainless steel, with Ex d magnet system
M...C 510 ... TT __ Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system

Name	Description
M...C 510 ... TT AIR __ Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 510 ... NT __ Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system
M... 511 ...	Pilot operated 5/2-way solenoid valves, with combined spring return
M... 511 ... VES	Pilot operated 5/2-way solenoid valves, with combined spring return, stainless steel
M... 511 ... TT	Pilot operated 5/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)
M... 511 ... TT AIR	Pilot operated 5/2-way solenoid valves, with combined spring return, for low temperature (with bidirectional sealing)
M... 511 ... HT	Pilot operated 5/2-way solenoid valves, with combined spring return, for high temperature
M... 511 ... NT	Pilot operated 5/2-way solenoid valves, with combined spring return, for -20°C
M... 511 ... NTB	Pilot operated 5/2-way solenoid valves, with combined spring return, for -25°C
M...C 511 ...	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return
M...C 511 ... VES	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel
M...C 511 ... TT	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)
M...C 511 ... TT AIR	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with bidirectional sealing)
M...C 511 ... NT	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C
M... 511 ... __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with Ex d magnet system
M... 511 ... VES __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system
M...C 511 ... TT __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 511 ... TT AIR __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 511 ... NT __ Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system

Table 12 [V12] Pilot operated 5/3-way solenoid valves

Placeholder “__” for 24VDC, 110 VAC, 230 VAC.

Name	Description
M... 53. ...	Pilot operated 5/3-way solenoid valves
M... 53. ... VES	Pilot operated 5/3-way solenoid valves, stainless steel
M... 53. ... TT	Pilot operated 5/3-way solenoid valves for low temperature (with unidirectional sealing)
M... 53. ... TT AIR	Pilot operated 5/3-way solenoid valves for low temperature (with bidirectional sealing)
M... 53. ... HT	Pilot operated 5/3-way solenoid valves for high temperature
M... 53. ... NT	Pilot operated 5/3-way solenoid valves for -20°C
M...C 53. ...	Pilot operated 5/3-way solenoid valves with CNOMO interface
M...C 53. ... VES	Pilot operated 5/3-way solenoid valves with CNOMO interface, stainless steel
M...C 53. ... TT	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)
M...C 53. ... TT AIR	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)
M...C 53. ... NT	Pilot operated 5/3-way solenoid valves with CNOMO interface, for -20°C
M... 53. ... __ Ex d	Pilot operated 5/3-way solenoid valves with Ex d magnet system
M... 53. ... VES __ Ex d	Pilot operated 5/3-way solenoid valves, stainless steel, with Ex d magnet system
M...C 53. ... TT __ Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system
M...C 53. ... TT AIR __ Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system
M...C 53. ... NT __ Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system

Table 13 [V13] Pilot operated 2/2-way solenoid valves with auxiliary control air

Name	Description
MEH 211 ...	Pilot operated 2/2-way solenoid valves with auxiliary control air
MEH 211 ... VES	Pilot operated 2/2-way solenoid valves with auxiliary control air, stainless steel
MEH 211 ... TT	Pilot operated 2/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
MEH 211 ... HT	Pilot operated 2/2-way solenoid valves with auxiliary control air, for high temperature
MEH 211 ... NT	Pilot operated 2/2-way solenoid valves, with auxiliary control air for -20°C

Table 14 [V14] Pilot operated 3/2-way solenoid valves with auxiliary control air

Name	Description
M...EH 311 ...	Pilot operated 3/2-way solenoid valves with auxiliary control air
M...EH 311 ... VES	Pilot operated 3/2-way solenoid valves with auxiliary control air, stainless steel
M...EH 311 ... TT	Pilot operated 3/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
M...EH 311...TT AIR	Pilot operated 3/2-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
M...EH 311 ... HT	Pilot operated 3/2-way solenoid valves with auxiliary control air, for high temperature
M...EH 311 ... NT	Pilot operated 3/2-way solenoid valves, with auxiliary control air for -20°C

Table 15 [V15] Pilot operated 5/2-way solenoid valves with auxiliary control air

Name	Description
M...EH 511 ...	Pilot operated 5/2-way solenoid valves with auxiliary control air
M...EH 511 ... VES	Pilot operated 5/2-way solenoid valves with auxiliary control air, stainless steel
M...EH 511 ... TT	Pilot operated 5/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
M...EH 511 ... TT AIR	Pilot operated 5/2-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
M...EH 511 ... HT	Pilot operated 5/2-way solenoid valves with auxiliary control air, for high temperature
M...EH 511 ... NT	Pilot operated 5/2-way solenoid valves, with auxiliary control air for -20°C

Table 16 [V16] Pilot operated 5/3-way solenoid valves with auxiliary control air

Name	Description
M...EH 53. ...	Pilot operated 5/3-way solenoid valves with auxiliary control air
M...EH 53. ... VES	Pilot operated 5/3-way solenoid valves with auxiliary control air, stainless steel
M...EH 53. ... TT	Pilot operated 5/3-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
M...EH 53. ... TT AIR	Pilot operated 5/3-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
M...EH 53. ... HT	Pilot operated 5/3-way solenoid valves with auxiliary control air, for high temperature
M...EH 53. ... NT	Pilot operated 5/3-way solenoid valves, with auxiliary control air for -20°C

A number of logic-elements, bi-stable and quick-exhaust variants were also subject of the assessment for Systematic Capability. As they share the same development process, verification and testing as the Variants listed above in Tables 1 - 16, the Logic-elements, bi-stable and quick-exhaust variants meet the same requirements for Systematic Capability as the variants. However, these Logic-elements, bi-stable and quick-exhaust variants are not generally suitable for safety applications, so no FMEDA analysis was done for these variants.



3.1 Hardware Version Numbers

This assessment is applicable to the hardware versions of the Solenoid valves as documented in the corresponding drawing – see [D26] – [D142] for details.

4 IEC 61508 Functional Safety Assessment Scheme

exida assessed the development process used by HAFNER Pneumatika Kft. for this development project against the objectives of the *exida* certification scheme which includes subsets of IEC 61508 -1 and 2. The results of the assessment are documented in [R1] to [R5].

4.1 Methodology

The full functional safety assessment includes an assessment of all fault avoidance and fault control measures during hardware development and demonstrates full compliance with IEC 61508 to the end-user. The assessment considers all requirements of IEC 61508. Any requirements that have been deemed not applicable have been marked as such in the full Safety Case report, e.g. software development requirements for a product with no software. The assessment also includes a review of existing manufacturing quality procedures to ensure compliance to the quality requirements of IEC 61508.

As part of the IEC 61508 functional safety assessment the following aspects have been reviewed:

- Development process, including:
 - Functional Safety Management, including training and competence recording, FSM planning, and configuration management
 - Specification process, techniques and documentation
 - Design process, techniques and documentation, including tools used
 - Validation activities, including development test procedures, test plans and reports, production test procedures and documentation
 - Verification activities and documentation
 - Modification process and documentation
 - Installation, operation, and maintenance requirements, including user documentation
- Product design
 - Hardware architecture and failure behavior, documented a FMEDA

The review of the development procedures is described in section 5. The review of the product design is described in section 5.2.

4.2 Assessment level

The Solenoid valves has been assessed per IEC 61508 to the following level:

- SIL 3 capability

The development procedures have been assessed as suitable for use in applications with a maximum Safety Integrity Level of 3 (SIL3) according to IEC 61508.

5 Results of the IEC 61508 Functional Safety Assessment

exida assessed the development process used by HAFNER Pneumatika Kft. for these products against the objectives of IEC 61508 parts 1 - 3.

The assessment was done in June - November 2016 and documented in the SafetyCase [R2]. The surveillance audits were done in October 2019 and in July 2023.

5.1 Lifecycle Activities and Fault Avoidance Measures

HAFNER Pneumatika Kft. have a defined product lifecycle process in place. This is documented in the Quality Manual [D1] and the referenced documents therein. A documented modification process is also covered in the Quality Manual. No software is part of the design and therefore any requirements specific from IEC 61508 to software and software development do not apply.

The assessment investigated the compliance with IEC 61508 of the processes, procedures and techniques as implemented for product design and development. The investigation was executed using subsets of the IEC 61508 requirements tailored to the SIL 3 work scope of the development team. The result of the assessment can be summarized by the following observations:

The audited HAFNER Pneumatika Kft. design and development process complies with the relevant managerial requirements of IEC 61508 SIL 3.

5.1.1 Functional Safety Management

FSM Planning

HAFNER Pneumatika Kft. have a defined process in place for product design and development. Required activities are specified along with review and approval requirements. The different phases together with the corresponding work items and their required input and output is defined. It also contains references to other planning documents where the verification and validation activities and methods are defined. The roles and responsibilities are also defined herein.

Sample documents have been reviewed and found to be sufficient. The modification process is covered by the Quality manual [D1]. This process and the procedures referenced therein fulfill the requirements of IEC 61508 with respect to functional safety management for a product with simple complexity and well defined safety functionality.

Version Control

The Quality manual [D1] requires that all documents and drawings are under version control. They are stored in the ERP system with full version management. All of the server discs also have daily backups and it's simple to restore a file from one of the backups as shown in the audit.

Which versions of a work product was part of which test run is documented in the respective test report [D22].

Training, Competency recording

In the personal profile, kept at the HR department, the different training courses / seminars of each individual together with the official education are documented. Given that the development department is small; all projects always have access to the developers which have a long experience from similar projects at HAFNER Pneumatika Kft..

5.1.2 Safety Requirements Specification and Architecture Design

The requirements for the Solenoid valves are based on the customer or in-house requirements [D18] which includes the safety related requirements. As the design is simple and based upon standard designs with extensive field history, no semi-formal methods are needed. General Design and testing methodology is documented and required as part of the design process. This meets SIL 3.

5.1.3 Hardware Design

The design process is documented in the Quality manual [D1]. Items from IEC 61508-2, Table B.2 include observance of guidelines and standards, project management, documentation (design outputs are documented per quality procedures), structured design, modularization, use of well-tried components computer-aided design tools. This meets SIL 3.

5.1.4 Validation

Validation Testing is documented in the General test procedures [D1]. The test plan includes testing per all standard and customer performance requirements. As the Solenoid valves are purely mechanical devices with a simple safety function, there is no separate integration testing necessary. The Solenoid valves perform only 1 Safety Function, which is extensively tested under various conditions during validation testing.

Items from IEC 61508-2, Table B.3 include functional testing, project management, documentation, and black-box testing (for the considered devices this is similar to functional testing). Field experience and statistical testing via regression testing are not applicable. This meets SIL 3.

Items from IEC 61508-2, Table B.5 included functional testing and functional testing under environmental conditions, project management, documentation, failure analysis (analysis on products that failed), expanded functional testing, black-box testing, and fault insertion testing. This meets SIL 3.

5.1.5 Verification

The development and verification activities are defined in the Quality manual [D1]. For each design phase the objectives are stated, required input and output documents and review activities. This meets SIL 3.

5.1.6 Modifications

A modification procedure is defined in the Quality manual. This is implemented for product changes starting with formal validation tests as there is no integration test planned for this Type A product. The defined modification procedure, containing a procedure for Impact Analysis including checklists, in combination with the generic development model fulfils the objectives of IEC 61508.

All error reports are collected by the quality responsible and discussed in the weekly group meetings where all teams are present. All changes are first reviewed and analyzed for impact before being approved. Measures to verify and validate the change are developed following the normal design process.

As part of the *exida* scheme a surveillance audit is conducted every 3 years. The modification documentation listed below is submitted as part of the surveillance audit. *exida* will review the decisions made by the competent person in respect to the modifications made.

- List of all anomalies reported
- List of all modifications completed
- Safety impact analysis which shall indicate with respect to the modification:

- The initiating problem (e.g. results of root cause analysis)
 - The effect on the product / system
 - The elements/components that are subject to the modification
 - The extent of any re-testing
- List of modified documentation
 - Regression test plans

This meets SIL 3.

5.1.7 User documentation

HAFNER Pneumatika Kft. create the following user documentation: product catalogs, an Instruction manual and a Safety Manual [D25]. The Safety Manual was found to contain all of the required information given the simplicity of the products. The Safety Manual references the FMEDA reports which are available and contain the required failure rates, failure modes, useful life, and suggested proof test information.

Items from IEC 61508-2, Table B.4 include operation and maintenance instructions, user friendliness, maintenance friendliness, project management, documentation and limited operation possibilities (Solenoid valves perform well-defined actions)

This meets SIL 3.

5.2 Hardware Assessment

To evaluate the hardware design of the Solenoid valves Failure Modes, Effects, and Diagnostic Analysis's were performed by *exida*. The results were analyzed and reviewed by *exida* and is documented in the FMEDA report [R4].

A Failure Modes and Effects Analysis (FMEA) is a systematic way to identify and evaluate the effects of different component failure modes, to determine what could eliminate or reduce the chance of failure, and to document the system in consideration. An FMEDA (Failure Mode Effect and Diagnostic Analysis) is an FMEA extension. It combines standard FMEA techniques with extension to identify online diagnostics techniques and the failure modes relevant to safety instrumented system design.

From the FMEDA, failure rates are derived for each important failure category. All failure rate analysis results and useful life limitations are listed in the FMEDA report It list failure rates for the Solenoid valves. The failure rates listed are valid for the useful life of the device.

According to IEC 61508 the architectural constraints of an element must be determined. This can be done by following the 1_H approach according to 7.4.4.2 of IEC 61508 or the 2_H approach according to 7.4.4.3 of IEC 61508.

The 1_H approach involves calculating the Safe Failure Fraction for the entire element.

The 2_H approach involves assessment of the reliability data for the entire element according to 7.4.4.3.3 of IEC 61508.

The failure rate data used for this analysis meets the *exida* criteria for Route 2_H. Therefore, the Solenoid valves can be classified as 2_H devices. When 2_H data is used for all of the devices in an element, the element meets the hardware architectural constraints up to SIL 2 at HFT=0 (or SIL 3 @ HFT=1) per Route 2_H.

If Route 2_H is not applicable for the entire final element, the architectural constraints will need to be evaluated per Route 1_H.

Note, as the Solenoid valves are only one part of a (sub)system, the SFF should be calculated for the entire final element combination.

These results must be considered in combination with PFD_{avg} / PFH values of other devices of a Safety Instrumented Function (SIF) in order to determine suitability for a specific Safety Integrity Level (SIL). The architectural constraints requirements of IEC 61508-2, Table 2 also need to be evaluated for each final element application. It is the end-users responsibility to confirm this for each particular application and to include all components of the final element in the calculations.

The analysis shows that the design of the Solenoid valves can meet the hardware requirements of IEC 61508, SIL 3 depending on the complete final element design. The Hardware Fault Tolerance and PFD_{avg} / PFH requirements of IEC 61508 must be verified for each specific design.

5.2.1 Failure rates

The table below lists the failure rates in FIT (failures / 10^9 hours) for the Solenoid valves. The variants are described in chapter 3.

Table 17: Failure rates per IEC 61508:2010

Variant	Profile	exida Profile		
		Failure rates (in FIT)		
		λ_{SD}	λ_{DD}	λ_{DU}
[V1]	5	3	0	377
[V2]	5	3	0	545
[V3]	5	75	0	7
[V4]	5	55	0	330
[V5]	5	55	0	470
[V6]	5	96	0	502
[V7]	5	55	0	540
[V8]	5	111	0	870
[V9]	5	159	0	206
[V10]	5	150	0	230
[V11]	5	150	0	470
[V12]	5	280	0	504
[V13]	5	159	0	280
[V14]	5	145	0	331
[V15]	5	145	0	471
[V16]	5	269	0	504

6 IEC 61508 Functional Safety Surveillance Audit

6.1 Roles of the parties involved

HAFNER Pneumatika Kft.	Manufacturer of the Solenoid valves
<i>exida</i>	Performed the hardware assessment
<i>exida</i>	Performed the IEC 61508 Functional Safety Surveillance Audit per the accredited <i>exida</i> scheme.

6.2 Surveillance Methodology

As part of the IEC 61508 functional safety surveillance audit the following aspects have been reviewed:

- Procedure Changes – Changes to relevant procedures since the last audit are reviewed to determine that the modified procedures meet the requirements of the *exida* certification scheme.
- Engineering Changes – The engineering change list is reviewed to determine if any of the changes could affect the safety function of the Solenoid valves.
- Impact Analysis – If changes were made to the product design, the impact analysis associated with the change will be reviewed to see that the functional safety requirements for an impact analysis have been met.
- Field History – Shipping and field returns during the certification period will be reviewed to determine if any systematic failures have occurred. If systematic failures have occurred during the certification period, the corrective action that was taken to eliminate the systematic failure(s) will be reviewed to determine that said action followed the approved processes and was effective.
- Safety Manual – The latest version of the safety manual will be reviewed to determine that it meets the IEC 61508 requirements for a safety manual.
- FMEDA Update – If required or requested the FMEDA will be updated. This is typically done if there are changes to the IEC 61508 standard and/or changes to the *exida* failure rate database.
- Evaluate use of the certificate and/or certification mark - Conduct a search of the applicant's web site and document any misuse of the certificate and/or certification mark. Report any misuse of the certificate and/or certification mark to the *exida* Managing Director.
- Recommendations from Previous Audits – If there are recommendations from the previous audit, these are reviewed to see if the recommendations have been implemented properly.

6.3 Surveillance Results 2019

HAFNER contracted *exida* in March 2019 to perform the surveillance audit for the above Solenoid valves. The surveillance audit was conducted onsite at the HAFNER Pneumatika Kft.'s facility in Halászi on October 15 – 16 2019

6.3.1 Procedure Changes

There were no changes to the procedures during the previous certification period.

6.3.2 Engineering Changes

There were no significant design changes to the certified products during the previous certification period. Three new / modified valves have been added, MEH, TT AIR and MH311, all treated as modification of existing valves.

The change documentation was reviewed and all documentation was found to be acceptable.

6.3.3 Impact Analysis

There were no safety-related design changes during the previous certification period.

6.3.4 Field History

The field histories of these products were analyzed and found to be consistent with the failure rates predicted by the FMEDA.

6.3.5 Safety Manual

No changes to the initial assessed safety manual had been done. The current version is compliant with IEC 61508:2010.

6.3.6 FMEDA Update

The FMEDA was updated as part of this project to add the MEH, TT AIR and MH311 types.

6.3.7 Evaluate use of certificate and/or certification mark

The HAFNER website was searched and no misleading or misuse of the certification or certification marks was found.

6.3.8 Previous Recommendations

There were no previous recommendations to be assessed at this audit.

6.4 Surveillance Results 2023

HAFNER contracted *exida* in April 2023 to perform the surveillance audit for the above Solenoid valves. The surveillance audit was conducted onsite at the HAFNER Pneumatika Kft.'s facility in Halászi on July 18 – 19 2023

6.4.1 Procedure Changes

There were no changes to the procedures during the previous certification period.

6.4.2 Engineering Changes

There were no significant design changes to the previously certified products during the previous certification period. New / modified valves have been added, all being subject of updated FMEDAs and treated as modification of existing designs.

The change documentation was reviewed and all documentation was found to be acceptable.

6.4.3 Impact Analysis

There were no safety-related design changes during the previous certification period.

6.4.4 Field History

The field histories of these products were analyzed and found to be consistent with the failure rates predicted by the updated FMEDA. No increase in systematic and random failures is visible.

6.4.5 Safety Manual

No changes to the initial assessed safety manual have been done. The current version is compliant with IEC 61508:2010.

6.4.6 FMEDA Update

As part of the HW assessment, the FMEDA and FMEDA report were updated with the new valve variants and restructuring the valves into the 16 variant groups.

6.4.7 Evaluate use of certificate and/or certification mark

The HAFNER website was searched and no misleading or misuse of the certification or certification marks was found.

6.4.8 Previous Recommendations

The previous recommendations were closed and one new added.

6.4.9 Surveillance Audit Conclusion

The result of the Surveillance Audit Assessment can be summarized by the following observations:



The HAFNER Pneumatika Kft. Solenoid valves continues to meet the relevant requirements of IEC 61508:2010 for SIL 3 in low demand applications based on the initial assessment and considering:

- field failure history
- permitted modifications completed on the product

This conclusion is supported by the updated certification documents.

7 Terms and Definitions

Architectural Constraint	The SIL limit imposed by the combination of SFF and HFT for Route 1 _H or by the HFT and Diagnostic Coverage (DC applies to Type B only) for Route 2 _H
<i>exida</i> criteria	A conservative approach to arriving at failure rates suitable for use in hardware evaluations utilizing the 2 _H Route in IEC 61508-2.
Fault tolerance	Ability of a functional unit to continue to perform a required function in the presence of faults or errors (IEC 61508-4, 3.6.3)
FIT	Failure In Time (1×10^{-9} failures per hour)
FMEDA	Failure Mode Effect and Diagnostic Analysis
HFT	Hardware Fault Tolerance
Low demand mode	Mode, where the demand interval for operation made on a safety-related system is greater than twice the proof test interval.
PFD _{avg}	Average Probability of Failure on Demand
Random Capability	The SIL limit imposed by the PFD _{avg} for each element.
SFF	Safe Failure Fraction summarizes the fraction of failures, which lead to a safe state and the fraction of failures which will be detected by diagnostic measures and lead to a defined safety action.
SIF	Safety Instrumented Function
SIL	Safety Integrity Level
SIS	Safety Instrumented System – Implementation of one or more Safety Instrumented Functions. A SIS is composed of any combination of sensor(s), logic solver(s), and final element(s).
Systematic Capability	The SIL limit imposed by the capability of the products manufacturer.
Type A element	“Non-Complex” element (using discrete components); for details see 7.4.4.1.2 of IEC 61508-2
Type B element	“Complex” element (using complex components such as micro controllers or programmable logic); for details see 7.4.4.1.3 of IEC 61508-2

8 Status of the Document

8.1 Liability

exida prepares reports based on methods advocated in International standards. *exida* accepts no liability whatsoever for the use of this report or for the correctness of the standards on which the general calculation methods are based.

8.2 Releases

Contract Number	Report Number	Revision Notes
Q23/04-151-C	1511-126-C R003 V3, R1	Naming corrected for M... and P...
Q23/04-151-C	1511-126-C R003 V3, R0	Surveillance audit 2023 New grouping structure implemented.
Q19/02-018-C	1511-126-C R003 V2, R0	Surveillance audit and new versions added: MEH, TT AIR and MH 311
Q15/11-126-C	1511-126-C R003 V1, R0	Review comments implemented.
Q15/11-126-C	1511-126-C R003 V0, R2	Bistable versions added
Q15/11-126-C	1511-126-C R003 V0, R1	Draft; Waiting for review

Author: Peter Söderblom


Review: Steven Close, V2 R0
Jürgen Hochhaus, V3 R0

Release status: Released 09-Jan-2020, V2 R0
24-Jan-2024, V3 R0
30-Jan-2024, V3 R1

8.3 Future Enhancements

At request of client.

8.4 Release Signatures



Peter Söderblom, Senior Safety Engineer



Jürgen Hochhaus, Senior Safety Engineer